

## SIGNAL TOWER FOR EXPLOSION PROOF APPLICATION



- High protection rating IP 65
- Signal tower system 70 mm Ø with modular construction
- Improved illumination
- Flexible combination of optical and audible elements
- Life duration up to 50,000 hrs

### Marking:

**Ex** II 3G Ex nA IIA T5 Tamb : -20°C/ + 50°C

### Label:

<p><b>GRAF</b> AUTOMATION &amp; PROCESS SOLUTION</p>	<p>www.grafspa.it Via G. Galilei 32 41015 Nonantola (MO) Italy</p>	<p>NON APRIRE ELEMENTI BLOCCATI DO NOT OPEN ELEMENTS BLOCKED</p>	
<p><b>Ex nA II T5</b></p>	<p>-20°C &lt; Ta &lt; 50°C</p>	<p>24V AC/DC 0,06A IP65</p>	

Technical Specification	
Electrical	
	<b>LED Permanent light element (Red, Green)</b>
<b>Power Supply</b>	24 Vdc
<b>Current Consumption</b>	< 30 mA (each light element)
Mechanical	
<b>Housing:</b>	Terminal element: PA fibreglass, high-impact Cap: PC
<b>Lens:</b>	PC, transparent

<b>Fixing:</b>	Tube mounting: diameter of insertion Ø 35 mm
<b>Cable entry:</b>	Pre-cabled - standard length cable 2mt
<b>Element seal:</b>	Pre-mounted with each module
<b>Protection rating:</b>	Light elements: IP 65
<b>Service Temperature</b>	- 20°C + 50°C

Dimension	Connection
-----------	------------

